Coast Guard, DOT §162.017–3

162.027-3 Approval procedures.

Subpart 162.028—Extinguishers, Fire, Portable, Marine Type

162.028-1 Applicable specifications. 162.028-2 Classification.

162.028-3 Requirements.

162.028-4 Marine type label.

162.028-5 Independent laboratories: Listing.

162.028-6 Examinations, tests, and inspections.

162.028-7 Procedure for listing and labeling. 162.028-8 Termination of listing or labeling.

Subpart 162.039—Extinguishers, Fire, Semiportable, Marine Type

162.039-1 Applicable specifications.

162.039–2 Classification.

162.039-3 Requirements.

162.039-4 Marine type label.

162.039-5 Recognized laboratory.

162.039-6 Examinations, tests, and inspections.

162.039-7 Procedure for listing and labeling. 162.039-8 Termination of listing or labeling.

Subpart 162.050—Pollution Prevention Equipment

162.050-1 Scope.

162.050-3 Definitions.

162.050-4 Documents incorporated by reference.

162.050-5 Contents of application.

162.050-7 Approval procedures.

162.050-9 Test report.

162.050-11 Marking.

162.050-13 Factory production and inspection.

162.050-14 Sample collection and preservation.

162.050-15 Designation of facilities.

162.050-17 Separator test rig.

162.050-19 Monitor and bilge alarm test rig.

162.050-21 Separator: Design specification.

162.050–23 Separator: Approval tests.

162.050-25 Cargo monitor: Design specification.

162.050–27 Cargo monitor: Approval tests.

162.050-29 Bilge monitor: Design specifica-

162.050–31 Bilge monitor: Approval tests.

162.050-33 Bilge alarm: Design specification.

162.050-35 Bilge alarm: Approval tests.

162.050-37 Vibration test.

162.050-39 Measurement of oil content.

AUTHORITY: 33 U.S.C. 1321(j) 1903; 46 U.S.C. 3306, 3703, 4104, 4302; E.O. 12234, 45 FR 58801, 3 CFR, 1980 Comp., p. 277; E.O. 11735, 38 FR 21243, 3 CFR, 1971–1975 Comp., p. 793; 49 CFR 1.46.

Subpart 162.017—Valves, Pressure-Vacuum Relief, for Tank Vessels

Source: CGFR 50-9, 15 FR 1680, Mar. 25, 1950, unless otherwise noted.

§ 162.017-1 Applicable specifications.

- (a) There are no other specifications applicable to this subpart.
- (b) [Reserved]

§162.017-2 Type.

This specification covers the design and construction of pressure-vacuum relief valves intended for use in venting systems on all tank vessels transporting inflammable or combustible liquids.

[56 FR 35827, July 29, 1991]

§ 162.017-3 Materials, construction, and workmanship.

- (a) The valves shall be of substantial construction and first class workmanship and shall be free from imperfections which may affect its serviceability.
- (b) Bodies of pressure-vacuum relief valves must be made of bronze or such corrosion-resistant material as may be approved by the Commandant (G-MSE).
- (c) Valve discs, spindles, and seats shall be made of bronze or such corrosion--resistant material as may be approved by the Commandant.
- (d) Where springs are employed to actuate the valve discs, the springs shall be made of corrosion-resistant material. Springs plated with corrosion-resistant material are not acceptable.
- (e) Flame screens shall be made of corrosion-resistant wire.
- (f) Nonmetallic materials will not be permitted in the construction of the valves, except bushings used in way of moving parts and gaskets may be made of nonmetallic material resistant to attack by the product carried. Nonmetallic diaphragms will be allowed where diaphragm failure will not result in unrestricted flow of cargo vapors to the atmosphere nor in an increase in the pressure or vacuum at which the valve normally releases.
- (g) The design and construction of the valves shall permit overhauling